

## MINI / TQ SPINDLES

Note: Spindles, King Pins and King Pin Shims Sold Separately



Use 3006 or 4146 Hub

DESCRIPTION	P/N
7° Alum. Spindle / Steel Snout	BRP 2990
5/8" King Pin	BRP 4155
Replacement Bushing	BRP 4153
Replacement Snout	BRP 2990S
Castle Nut	BRP 4151
King Pin Shim - 5/8" X .150"	BRP 4156
King Pin Shim - 5/8" X .125"	BRP 4156-1



Use 3006 or 4146 Hub

DESCRIPTION	P/N
7° Alum. Spindle / Steel Snout	BRP 2994
11/16" King Pin	BRP 2996
Replacement Bushing	BRP 2991
Replacement Snout	BRP 2995
Castle Nut	BRP 4151



Use 3006 or 4146 Hub

DESCRIPTION	P/N
10° Alum. Spindle / Steel Snout	BRP 4152HD
5/8" X 3.650" King Pin	BRP 4155
Replacement Bushing	BRP 4153
Replacement Snout	BRP 4154
Spindle Castle Nut	BRP 4151
King Pin Shim - 5/8" X .150"	BRP 4156
King Pin Shim - 5/8" X .125"	BRP 4156-1
Left Front Steering Arm	BRP 4158
Right Front Steering Arm	BRP 4159



Use 4188 Hub

DESCRIPTION	P/N
10° Alum. Spindle / Steel Snout	BRP 4191
5/8" X 3.850" King Pin	BRP 4194
Replacement Bushing	BRP 4153
Replacement Snout	BRP 4192
Castle Nut	BOL 163F
King Pin Shim - 5/8" X .150"	BRP 4156
King Pin Shim - 5/8" X .125"	BRP 4156-1
Snap Ring	BRP 4193
Axle Eye	BRP 4163

## MINI / TQ ALUMINUM HUBS



DESCRIPTION	P/N
4 ON 4" Alum. Hub - 1/2"F Studs	BRP 3006
Dust Cap	BRP 3007
Tapered Outer Roller Bearing Assy.	BRP 3000
Inner Race	BRP 2998
Inner Bearing and Seal	BRP 2999



DESCRIPTION	P/N
4 ON 4" Alum. Hub - 1/2"F Studs	BRP 4188
Replacement Inner/Outer Bearing	BRP 4148
Replacement Stud	BRP 4190
1/2" C Narrow Nylock	BOL 083C
1/2"F Flanged Whiz Nut	BRP 4150



DESCRIPTION	P/N
4 ON 4" Alum. Hub - 1/2"F Studs (comes with hub, bearings, & cap)	BRP 4145
4 On 4" Alum. Hub Only	BRP 4146
Inner Bearing	BRP 4148
Outer Bearing	BRP 4149
Dust Cap	BRP 3007

## DIRECT MOUNT WHEEL CENTERS



DESCRIPTION	P/N
Front Aluminum Hub (fits BRP 4152HD hub)	BRP 4144



DESCRIPTION	P/N
Front Aluminum Hub (fits BRP 4191 hub)	BRP 4189



DESCRIPTION	P/N
Splined Aluminum Hub (fits all micro splined axles)	BRP 4131

## 1 1/4" REAR KEYED STEEL AXLES



DESCRIPTION	P/N
1 1/4" X .250" Wall 4130 Steel Keyed Axle - Available in the following lengths: 44", 46", and 48"	BRP 4097-length
1 1/4" X .188" Wall 4130 Steel Keyed Axle - Available in the following lengths: 35", 40", 42", and 44"	BRP 4321-length

# MINI / MICRO SPRINT

## KEYED HUBS AND ROTORS

### Rotors



DESCRIPTION	P/N
3/16" Rotor - 4 on 3" bolt Steel 8" diameter	<b>BRP 4177</b>
3/16" Drilled Rotor - 4 on 3" bolt Steel - 9 1/2" Diameter	<b>BRP 4178</b>

### 6 on 5 1/4" Sprocket Hubs



DESCRIPTION	P/N
1 1/4" Split Sprocket Hub	<b>BRP 4128</b>
1 3/8" Split Sprocket Hub	<b>BRP 4129</b>

### 4 on 4" Wheel Hubs



DESCRIPTION	P/N
1 1/4" Split Hub with 1/2" F Studs	<b>BRP 4134</b>
1 3/8" Split Hub with 1/2" F Studs	<b>BRP 4135</b>
1 1/2" Split Hub with 1/2" F Studs	<b>BRP 4136</b>

## REAR SPLINED MICRO SPRINT AXLE

### 1 3/4" Gundrilled Aluminum Axles



LENGTH	RH SPLINE LENGTH	LH SPLINE LENGTH	P/N
55" Long Splined Aluminum Axle	11"	14"	<b>BRP 4099</b>
54" Long Splined Aluminum Axle	17 1/4"	17 1/4"	<b>BRP 4098</b>
50" Long Splined Aluminum Axle	18"	18"	<b>BRP 4102</b>

### Micro Sprint Axle Spacers



Splined		Non Splined	
WIDTH	P/N	WIDTH	P/N
1/2"	<b>BRP 4114-1</b>	1/8"	<b>BRP 4094</b>
1"	<b>BRP 4114-3</b>	1/4"	<b>BRP 4094-1</b>
2"	<b>BRP 4114-6</b>	3/8"	<b>BRP 4094-2</b>
2 1/2"	<b>BRP 4114-7</b>	1/2"	<b>BRP 4094-3</b>
		3/4"	<b>BRP 4094-4</b>
		1"	<b>BRP 4094-5</b>
		1"	<b>BRP 4094-5R</b>
		1 1/2"	<b>BRP 4094-6</b>
		2"	<b>BRP 4094-7</b>
		2 1/2"	<b>BRP 4094-8</b>
		3"	<b>BRP 4094-9</b>
		3 1/4"	<b>BRP 4094-10</b>
		3 3/4"	<b>BRP 4094-11</b>
		4"	<b>BRP 4094-12</b>
		5"	<b>BRP 4094-13</b>
		6"	<b>BRP 4094-14</b>

DESCRIPTION	P/N
Splined Bearing Insert	<b>BRP 4115</b>
Splined Bearing Insert - Wide	<b>BRP 4116</b>
Taper Spacer to Seat Nut	<b>BRP 4113</b>



### Micro Sprint Hubs & Sprockets



DESCRIPTION	P/N
4 on 4" Splined Hub for 15° Nut	<b>BRP 4106</b>



DESCRIPTION	P/N
4 on 4" Splined Hub for 30° Nut	<b>BRP 4105</b>




DESCRIPTION	P/N
Splined Rotor Mount (Uses BRP 4177 & 4178 Rotor)	<b>BRP 4108</b>



DESCRIPTION	P/N
Splined Sprocket Hub - 6 on 5 1/4" 1.200" Wide with 1/4" F mounting holes	<b>BRP 4126</b>



DESCRIPTION	P/N
Splined Sprocket Hub - 6 on 5 1/4" 1.400" Wide with 1/4" F mounting holes	<b>BRP 4126-1</b>



### Micro Sprint Axle Nuts

DESCRIPTION	P/N
15° Taper Right Hand Nut (Stallard)	<b>BRP 4110</b>
15° Taper Left Hand Nut (Stallard)	<b>BRP 4111</b>
30° Taper Right Hand Nut	<b>BRP 4110-1</b>
30° Taper Left Hand Nut	<b>BRP 4111-1</b>
Flat End Right Hand Nut (Lafier)	<b>BRP 4109</b>
Flat End Left Hand Nut (Lafier)	<b>BRP 4109-1</b>

## MINI SPRINT AXLE



LENGTH	RH SPLINE LENGTH	LH SPLINE LENGTH	P/N
48" Mini Sprint Axle (53" Overall)	16"	10"	BRP 2900

## MINI SPRINT AXLE

### Aluminum Axle Spacers



LENGTH	P/N
1/4"	BRP 2909
1/2"	BRP 2909-1
5/8"	BRP 2909-2
1"	BRP 2909-3
1.5"	BRP 2909-5
2"	BRP 2909-6
2 1/2"	BRP 2909-7
3"	BRP 2909-10

### Tapered Spacers



DESCRIPTION	P/N
Tapered Cone Spacer	BRP 2894
Female Taper to Flat Spacer	BRP 2908

### Bearing Inserts



DESCRIPTION	P/N
Aluminum Insert For 2910 Bearing	BRP 2905
Double Insert For BRP 2910 Bearing	BRP 2907
Single Insert For BRP 2910-1 Bearing	BRP 2906

## BIRDCAGE BEARINGS



DESCRIPTION	P/N
6011 Bearing for Use with BRP 2941	BRP 2910
6211 Bearing for Use with BRP 2096	BRP 2910-1
6010 Bearing	BRP 4124

## WING SLIDER



DESCRIPTION	P/N
Aluminum Wing Slider for 1" Tubing	BRP 4175

## TORSION STOPS



DESCRIPTION	P/N
7/8" Broach Aluminum Torsion Stop	BRP 2962
3/4" Broach Aluminum Torsion Stop	BRP 4172



### Sprocket Hubs

DESCRIPTION	P/N
6 on 5 1/4" Sprocket Hub (Hench Style)	BRP 2935



### Pin Splined Hubs

DESCRIPTION	P/N
4 on 4" Splined Hub with 1/2" F Studs	BRP 2930
Replacement 1/2" F Stud	BRP 2932
4 on 4" Hub with Drive Pins	BRP 2936
4 on 4" Pressure Plate	BRP 2936-1
3/8" Nylock for replacement Pin	BRP 2917



### Rear Axle Nuts

DESCRIPTION	P/N
1 7/8" Right Hand Axle Nut	BRP 2892
1 7/8" Left Hand Axle Nut	BRP 2893

## MINI SPRINT ROTORS



DESCRIPTION	P/N
Drilled Rotor - 10" Diameter Steel X .320" Thick (2" Spline)	BRP 63
Drilled Rotor - 10" Diameter Aluminum X .375" Thick (2" Spline)	BRP 63A

## TORSION ARMS



DESCRIPTION	BROACH	P/N
5/8" Front Torsion Arm Blank	3/4"	BRP 4170
1/2" Thick X 15 1/2" Long Torsion Arm Blank	3/4"	BRP 4164
5/8" Thick X 15 1/2" Long Torsion Arm Blank	7/8"	BRP 4165-1